

BLAZER

400 VA ~ 2000 VA




Features

- LED display or LCD display selectable
- Microprocessor-based digital control
- Boost and buck AVR for voltage stabilization
- Auto sensing frequency
- Wide input voltage range
- Power-on self test
- Cold start
- Auto restart when mains power is restored
- Auto track mains phase to ensure that inverter output voltage has same phase with utility voltage, reducing transfer time and peak surge
- Intelligent battery management: battery temperature compensation to extend the battery life; three-stage charging to shorten recharge time
- Short circuit, battery overcharge / overdischarge, overload, surge protections
- Automatic charging in OFF mode
- Optional no-load shutdown
- Optional RS232 / USB communication port and RJ11 / RJ45 protection
- Unattended safety shutdown: system alarm and auto Power-On / Off by RS232 or USB interface communicating with PC

Rear Panel

1. Output Socket (selectable)
2. TEL/Modem/Fax surge protection (optional)
3. USB (optional)
4. AC Input
5. Fuse



Optional sockets



400 VA ~ 800 VA

1200 VA ~ 1500 VA

1500 VA ~ 2000 VA

Specifications

MODEL	EA240	EA260	EA280	EA2120	EA2150	EA2200
Capacity	400 VA 240 W	600 VA 360 W	800 VA 480 W	1200 VA 720 W	1500 VA 900 W	2000 VA 1200 W
INPUT						
Voltage	100 V / 110 V / 120 V; 80 ~ 150 Vac; 220 V / 230 V / 240 V; 162 ~ 295 Vac (220 V: 145 ~ 295 Vac optional)					
Frequency	50 / 60 Hz ± 10% (auto-sense)					
OUTPUT						
Voltage	100 V / 110 V / 120 Vac ± 10% or 220 V / 230 V / 240 Vac ± 10%					
Frequency	50 / 60 Hz ± 1% (auto-sense)					
Waveform	Mains mode: pure sine wave; Battery mode: simulated sine wave					
Transfer time	2 ~ 7 ms (typical), 10 ms (max.)					
BATTERIES						
DC voltage	12 V			24 V		
Configuration	12 V / 4.5 Ah×1	12 V / 7.0 Ah×1	12 V / 8.0 Ah×1	12 V / 7.0 Ah×2	12 V / 8.0 Ah×2	12 V / 9.0 Ah×2
Recharge time	6 ~ 8 h					
OTHERS						
Protections	Short circuit - battery overcharge - overdischarge - overload - surge					
USB / RS232 / SNMP (optional)	Support Windows 98 / 2000 / 2003 / XP / Vista / 2008 / Windows 7 / 8 / 10					
Humidity	20 ~ 90% RH @ 0 ~ 40°C (non-condensing)					
Noise level	≤ 45 dB (1 m)					
Plastic case	Net / Gross weight (kg)	3.7 / 4.0	4.3 / 4.6	5.2 / 5.5	8.6 / 9.0	10.1 / 10.5
	Dimensions (W × D × H) (mm)	100 × 290 × 140			140 × 345 × 170	
	Packaged dimensions (W × D × H) (mm)	139 × 335 × 210			198 × 406 × 245	
	Quantity / 20 ft	2300 pcs			1000 pcs	
Metal case	Net / Gross weight (kg)	/	5.1 / 5.4	6.3 / 6.6	9.6 / 10.1	11.3 / 11.7
	Dimensions (W × D × H) (mm)	/	95 × 320 × 160		125 × 320 × 225	
	Packaged dimensions (W × D × H) (mm)	/	145 × 375 × 230		180 × 390 × 295	
	Quantity / 20 ft	/	2000 pcs		1000 pcs	
Rack mount	Net / Gross weight (kg)	/	7.0 / 7.5	8.2 / 8.7	11.6 / 12.1	13.3 / 13.8
	Dimensions (W × D × H) (mm)	/	308 × 438 × 88			308 × 438 × 132
	Packaged dimensions (W × D × H) (mm)	/	395 × 525 × 185			395 × 525 × 225

- All specifications subject to change without notice.
- Custom-made specifications are acceptable.